

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name Not applicable.

CAS No. Mixture

Trade Name DuPont™ Non-Stick Dry Film with Teflon® Fluoropolymer - Liquid

Product Code Non

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Lubricant
Uses Advised Against None

Company Identification Dentalight, inc

265 Grand Valley dr. Talbott, TN 37877

Telephone

E-Mail (competent person)

Emergency telephone number

Emergency Phone No.

865-674-0378

dentalight@gmail.com

Medical Emergency: PROSAR 24 hr: 1-800-217-5157 / 1-651-523-(

Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1

(703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Label elements

Hazard Symbol

Flam. Lig. 2; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; Asp. Tox. 1



Signal Word(s)

Hazard Statement(s)

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes serious eye irritation.

Causes skin irritation.

May cause drowsiness or dizziness.

Precautionary Statement(s) Keep away from heat/sparks/open flames/hot surfaces. - No

smoking. Keep container tightly closed. Wash hands and exposed skin after use.

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician. Do NOT induce vomiting.

Keep out of reach of children.

Other hazards

Revision: April 15, 2015 Page: 1/7

None



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt.	CAS No.	
Isopropanol	55 - 65	64-67-0	
Heptane, branched, cylic and linear	25 - 35	426260-76-6	

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation Move person to fresh air. If breathing is labored, administer oxygen. If

symptoms develop, obtain medical attention.

Skin Contact Wash affected skin with soap and water. If irritation (redness, rash, blistering)

develops, get medical attention. Take off contaminated clothing and wash it

before reuse.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists, get medical

advice/attention.

Ingestion Immediately call a POISON CENTER or doctor/physician. Do NOT induce

vomiting. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both

acute and delayed

May be fatal if swallowed and enters airways.

Indication of any immediate medical attention

and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media Extinguish with carbon dioxide, dry chemical, foam or water spray.

-Unsuitable Extinguishing Media Do not use water jet.

Special hazards arising from the substance or

mixture

Advice for fire-fighters

Highly flammable vapor (flash point below 23°C).

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying

with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapours.

Environmental precautions

Prevent liquid entering sewers, basements and workpits.

Revision: April 15, 2015 Page: 2/7



Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for

disposal or recovery.

Reference to other sections Additional Information None None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking Ground/bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof electrical / ventilating / lighting / equipment. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Avoid breathing vapours.

Conditions for safe storage, including any incompatibilities

-Storage temperature Keep out of reach of children. Keep in a cool, well ventilated place.

Keep container tightly closed.

-Incompatible materials This product should be stored away from sources of strong heat or

oxidising chemicals.

Specific end use(s) Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

		(8hr	TWA)	(87	(EL)	
SUBSTANCE.	CAS No.	PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	Note:
Heptane, branched, cylic and linear	426260-76-6	500 ppm*	1500 mg/m ³			*n-heptane
Isopropanol	67-63-0	400 ppm	200 ppm		400 ppm	

Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 216 °C); NIOSH 1400 (Alcohols I

Exposure controls

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber). Check with protective equipment manufacturer's data.

Respiratory protection



In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Revision: April 15, 2015 Page: 3/7



Thermal hazards Not normally required.

Environmental Exposure Controls Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Color. White (Translucent)
Odor Petroleum spirit
Odor Threshold (ppm) Not available

pH (Value) Not available
Melting Point (°C) / Freezing Point (°C) Not available

Boiling point/boiling range (°C): 94 - 98 (201 - 208 °F)

Flash Point (°C) -8 (18 °F) Evaporation Rate Not available Flammability (solid, gas) Not applicable Explosive Limit Ranges Not available Vapour pressure (Pascal) Not available Not available Vapour Density (Air=1) Density (g/ml) Not available Solubility (Water) Insoluble Solubility (Other) Not available

Partition Coefficient (n-Octanol/water)

Auto Ignition Point ("C)

Decomposition Temperature ("C)

Kinematic Viscosity (cSt)

Explosive properties

Not available

<20 @ 40 "C

Not explosive.

Other information Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

Chemical stability Stable.

Possibility of hazardous reactions None anticipated.

Conditions to avoid Avoid contact with heat and ignition sources.

Incompatible materials Strong oxidising agents

Hazardous decomposition product(s) Carbon monoxide, Carbon dioxide, Acrid smoke, Other

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Toxicity - Substances in preparations / mixtures

Information on toxicological effects

Isopropanol (CAS# 67-63-0);

Oxidizing properties

Acute toxicity Oral: LD50 = 5.84 g/kg (rat)

Inhalation: LC50 > 1000 ppm (rat) 6 hour(s) Dermal: LD50 = 16.4 ml/kg (rabbit) 24 hour(s)

May cause drowsiness or dizziness.

Not oxidizing.

Irritation/Corrosivity Irritating to eyes.

Revision: April 15, 2015 Page: 4/7



Sensitization It is not a skin sensitizer.

NOAEL = 5,000 ppm (Inhalation) Repeated dose toxicity

May cause drowsiness or dizziness.

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity There is no evidence of mutagenic potential.

Not available Reproductive toxicity

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Oral: LD50 >5 g/kg-bw Acute toxicity

Dermal: LD50 > 2 g/kg-bw

Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Irritation/Corrosivity Causes skin irritation. Repeated exposure may cause skin

dryness or cracking. May cause eye irritation.

Sensitization It is not a skin sensitizer.

Repeated dose toxicity NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects)

LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects)

May cause drowsiness or dizziness.

Carcinogenicity No data. It is unlikely to present a carcinogenic hazard to

man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity

There is no evidence of mutagenic potential.

Toxicity for reproduction No information available

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Long Term

Isopropanol (CAS# 67-63-0):

Short term LC50 (96 hour): 10,000 mg/l (Fathead minnow (Pimephales promelas))

> LC50 24hour(s): >10,000 mg/l (Daphnia magna) NOEC: 3.37 µmol/l (Daphnia magna) (Growth rate)

Persistence and degradability Not available. Bioaccumulative potential Not available. Not available. Mobility in soil

Results of PBT and vPvB assessment Not classified as PBT or vPvB.

Other adverse effects None known.

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials;

Short term LL50 (96 hour): >13.4 mg/L (Oncorhynchus mykiss)

> EL50 (48 hour): 3 mg/l (Daphnia magna, mobility) EC50 (96 hour): 13 mg/l (Pseudokirchnerella subcapitata)

Long Term NOELR (28 days) 1.5 mg/l (Fish) QSAR

LOEC (21 days): 0.32 mg/l (Daphnia magna)

NOEL (96 hour) 6.3 mg/l (Algae)

Revision: April 15, 2015 Page: 5/7



Persistence and degradability
Bioaccumulative potential
Mobility in soil
Pessits of RRT and vRvR assessment

Results of PBT and vPvB assessment

Other adverse effects

Not available. Not available. Not available.

Not classified as PBT or vPvB.

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

	Land transport (U.S. DOT)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN number	1993	1993	1993
Proper Shipping Name	Flammable liquid, n.o.s. (Isopropanol and Heptanes)	Flammable liquid, n.o.s. (Isopropanol and Heptanes)	Flammable liquid, n.o.s. (Isopropanol and Heptanes)
Transport hazard class(es)	3	3	3
Packing group	II	H	H
Environmental hazards	No.	No.	No.
Special precautions for user	None assigned	None assigned	None assigned
The second secon			

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

TSCA 12(b) Export Notification: CAS 9002-84-0 Polytetrafluoroethylene

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	****		****

SARA 311/312 - Hazard Categories:

∀ Fire	Sudden Release	Reactivity		Chronic (delayed
--------	----------------	------------	--	------------------

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Isopropanol	67-63-0	59

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	****	****	

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None		****

Revision: April 15, 2015 Page: 6/7



SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16. Date of preparation: March 26, 2015

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Revision: April 15, 2015 Page: 7/7